

# E14/L150

Tipo : E14/L150

do: 14mm

Type :

## Omologazione Homologation

**PN**

## Coefficiente efflusso ridotto

**Low flow coefficient**

## Campo di taratura Setting range

E.D. 2014/68/EU  
IV Cat.(PED)

150

0,86

100,0 - 150,0 bar

EAC

150

0,86

100,0 - 150,0 bar

ATEX Ex II 2 G c

150

0,86

100,0 - 150,0 bar

ATEX Ex II 2 D c

150

0,86

100,0 - 150,0 bar

ASME VIII Div.1

/

/

/

Canadian Reg. CRN

/

/

/

## CONFIGURAZIONE - CONFIGURATION

## Materiale Material

**Ottone  
Brass**

**Mista Ottone-Acciaio  
inox  
Mixed Brass-Stainless  
steel**

**Acciaio inox  
Stainless steel**

## Modelli Model

Con ghiera  
With ring nut  
Senza Ghiera  
Without ring nut

Con ghiera  
With ring nut  
Senza Ghiera  
Without ring nut

Con ghiera  
With ring nut  
Senza Ghiera  
Without ring nut

/

/

/

/

/

/

/

/

/

/

/

/

/

/

/

## Sedi di Tenuta Seal System

N.B.R. (Std) -10 / + 100 °C

N.B.R. (Std) -10 / + 100 °C

N.B.R. (Std) -10 / + 100 °C

E.P.D.M. -50 / + 150 °C

E.P.D.M. -50 / + 150 °C

E.P.D.M. -50 / + 150 °C

VITON -20 / +200 °C

VITON -20 / +200 °C

VITON -20 / +200 °C

SILICONE -60 / +200 °C

SILICONE -60 / +200 °C

SILICONE -60 / +200 °C

TEFLON -196 / +250 °C

TEFLON -196 / +250 °C

TEFLON -196 / +250 °C

KALREZ -20 / +250 °C

KALREZ -20 / +250 °C

KALREZ -20 / +275 °C

/

Metal -196 / +250 °C

Metal -196 / +450 °C

## Connessione Entrata Inlet Connection

G.1" - 1"1/4 - 1"1/2

G.1" - 1"1/4 - 1"1/2

G.1" - 1"1/4 - 1"1/2

ISO228

ISO228

ISO228

R.1" - 1"1/4 - 1"1/2

R.1" - 1"1/4 - 1" 1/2

R.1" - 1"1/4 - 1" 1/2

1" - 1"1/4 - 1"1/2 NPT

1" - 1"1/4 - 1" 1/2 NPT

1" - 1"1/4 - 1" 1/2 NPT

DN25-32-40 PN16-160

1" - 1"1/2 Tri Clamp

1" - 1"1/2 Tri Clamp

1" - 1"1/4 - 1"1/2 150-

DN25-40 DIN405-11851

DN25-40 DIN405-11851

/

DN25-32 PN16-160

DN25-32 PN16-160

/

1" - 1"1/4 150-1500 lb

1" - 1"1/4 150-1500 lb

## Connessione Uscita Outlet Connection

G.1"1/2 ISO228

G.1"1/2 ISO228

G.1"1/2 ISO228

DN40 PN16-160

1"1/2 - 2" Tri Clamp

1"1/2 - 2" Tri Clamp

1"1/2 150-1500 lb

DN40 DIN405-11851

DN40 DIN405-11851

/

DN40 PN16-160

DN40 PN16-160

/

1"1/2 150-1500 lb

1"1/2 150-1500 lb

/

/

/

/

/

/

**A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPEL), TÜV, RINA, Bureau Veritas, ABS e Lloy**

*On request tests can be made by the most prestigious societies, such as: INAIL (area ISPELS), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.*

**Note:**